



**COMPONENT SPECIALISTS**

P.O. Box 500  
 899 S. Prairie Lane  
 Marshfield, MO 65706  
 Phone: (417)859-6067  
 Fax: (417)859-2109

Model: HITACHI 6005SC-Z

CAPACITY -1,000 BTU/Hr, 60 Hz. HITACHI 6005 COMPRESSOR, REFRIGERANT 22

SCT → SST	77	81	85	89	93	97	101	105	109	113	117	121	125	129	133	137	141	145
5	500.1	488.3	476.4	464.3	452.1	439.7	427.2	414.6	401.9	389.0	376.0	362.8	349.5	336.2	322.6	309.0	295.2	281.4
10	553.0	539.5	525.9	512.3	498.6	484.8	471.0	457.0	443.0	428.9	414.8	400.5	386.1	371.7	357.1	342.5	327.7	312.8
15	615.9	600.6	585.4	570.1	554.8	539.4	524.0	508.5	493.0	477.4	461.7	446.0	430.2	414.4	398.5	382.5	366.4	350.2
20	687.3	670.4	653.5	636.5	619.5	602.4	585.3	568.1	550.9	533.6	516.3	498.9	481.5	464.0	446.5	428.9	411.3	393.6
25	766.1	747.5	729.0	710.3	691.6	672.8	653.9	635.0	616.0	597.0	577.9	558.7	539.6	520.3	501.1	481.8	462.4	443.1
30	850.8	830.7	810.5	790.2	769.9	749.4	728.8	708.2	687.5	666.7	645.9	625.0	604.0	583.0	562.0	540.9	519.8	498.6
31	868.4	848.0	827.5	806.9	786.2	765.4	744.5	723.5	702.5	681.4	660.2	638.9	617.7	596.3	574.9	553.5	532.0	510.5
32	886.2	865.4	844.6	823.7	802.7	781.5	760.3	739.0	717.7	696.2	674.7	653.1	631.5	609.8	588.1	566.3	544.5	522.6
33	904.1	883.0	861.9	840.7	819.3	797.9	776.4	754.8	733.1	711.3	689.5	667.6	645.6	623.6	601.5	579.4	557.2	535.0
34	922.1	900.8	879.4	857.8	836.2	814.5	792.6	770.7	748.7	726.6	704.5	682.2	659.9	637.6	615.2	592.7	570.1	547.6
35	940.3	918.7	897.0	875.1	853.2	831.2	809.1	786.8	764.5	742.1	719.7	697.1	674.5	651.8	629.1	606.2	583.4	560.4
36	958.7	936.8	914.7	892.6	870.4	848.1	825.7	803.1	780.5	757.9	735.1	712.2	689.3	666.3	643.2	620.0	596.8	573.5
37	977.2	954.9	932.6	910.2	887.7	865.1	842.4	819.6	796.7	773.8	750.7	727.5	704.3	681.0	657.6	634.1	610.5	586.9
38	995.7	973.2	950.7	928.0	905.2	882.3	859.3	836.3	813.1	789.9	766.5	743.1	719.5	695.9	672.2	648.4	624.5	600.5
39	---	991.7	968.8	945.8	922.8	899.6	876.4	853.1	829.7	806.1	782.5	758.8	735.0	711.1	687.0	662.9	638.7	614.3
40	---	1010.2	987.0	963.8	940.5	917.1	893.6	870.0	846.4	822.6	798.7	774.7	750.6	726.4	702.1	677.7	653.1	628.5
41	---	1028.7	1005.3	981.9	958.3	934.7	911.0	887.1	863.2	839.2	815.1	790.9	766.5	742.1	717.5	692.7	667.8	642.8
42	---	1047.4	1023.7	1000.0	976.2	952.4	928.4	904.4	880.3	856.0	831.7	807.2	782.6	757.9	733.0	708.0	682.8	657.4
43	---	1066.2	1042.2	1018.3	994.2	970.2	946.0	921.8	897.4	873.0	848.4	823.7	798.9	773.9	748.8	723.5	698.0	672.3
44	---	1084.9	1060.8	1036.6	1012.3	988.1	963.7	939.3	914.7	890.1	865.3	840.4	815.4	790.2	764.8	739.2	713.4	687.4
45	---	---	1079.4	1055.0	1030.5	1006.0	981.5	956.9	932.2	907.4	882.4	857.3	832.1	806.6	781.0	755.2	729.1	702.8
46	---	---	1098.0	1073.4	1048.7	1024.1	999.4	974.6	949.7	924.8	899.6	874.4	849.0	823.3	797.5	771.4	745.1	718.5
47	---	---	1116.7	1091.9	1067.0	1042.2	1017.4	992.4	967.4	942.3	917.1	891.6	866.0	840.2	814.2	787.9	761.3	734.4
48	---	---	1135.4	1110.4	1085.4	1060.4	1035.4	1010.4	985.2	960.0	934.6	909.1	883.3	857.3	831.1	804.6	777.7	750.5
49	---	---	1154.1	1128.9	1103.7	1078.6	1053.5	1028.4	1003.1	977.8	952.3	926.6	900.8	874.6	848.2	821.5	794.4	766.9
50	---	---	1172.8	1147.4	1122.1	1096.9	1071.7	1046.5	1021.1	995.7	970.2	944.4	918.4	892.1	865.6	838.6	811.3	783.6

Legend: SCT = Saturated Condensing Temperature, R-22.  
 SST = Saturated Suction Temperature, R-22.

- Notes: 1. Data subject to a +/- 5% tolerance.  
 2. Data based on 9 degrees Fahrenheit Subcooling & Superheat.  
 3. - - - indicates conditions outside of the approved operating range.  
 4. Operation outside the range of 14-46 deg F SST or 95-130 SCT is limited.  
 See ACCS publication **AC- 02- 006- 01- 0051** for details.



P.O. Box 500  
 899 S. Prairie Lane  
 Marshfield, MO 65706  
 Phone: (417)859-6067  
 Fax: (417)859-2109

Model: HITACHI 6005SC-Z

**COMPLEMENT SPECIALISTS**

AMPS -208V/3/60 Hz. HITACHI 6005 COMPRESSOR, REFRIGERANT 22

SCT →	77	81	85	89	93	97	101	105	109	113	117	121	125	129	133	137	141	145
SST																		
5	95.8	103.9	111.9	119.9	127.9	135.9	143.8	151.8	159.7	167.6	175.5	183.4	191.2	199.1	206.9	214.7	222.5	230.3
10	98.9	107.0	115.1	123.2	131.4	139.5	147.7	155.8	164.0	172.1	180.3	188.4	196.5	204.6	212.7	220.8	228.8	236.8
15	102.0	110.1	118.3	126.6	134.8	143.1	151.5	159.8	168.1	176.5	184.8	193.2	201.5	209.8	218.1	226.4	234.6	242.8
20	105.0	113.3	121.6	129.9	138.3	146.8	155.2	163.7	172.2	180.7	189.3	197.8	206.3	214.8	223.3	231.7	240.1	248.5
25	108.1	116.4	124.8	133.3	141.8	150.4	158.9	167.6	176.2	184.9	193.5	202.2	210.8	219.5	228.1	236.7	245.2	253.7
30	111.2	119.6	128.1	136.6	145.3	153.9	162.6	171.3	180.1	188.9	197.7	206.4	215.2	224.0	232.7	241.4	250.1	258.7
31	111.8	120.2	128.7	137.3	146.0	154.6	163.3	172.1	180.9	189.7	198.5	207.3	216.1	224.8	233.6	242.3	251.0	259.7
32	112.4	120.9	129.4	138.0	146.6	155.3	164.1	172.8	181.6	190.4	199.3	208.1	216.9	225.7	234.5	243.2	252.0	260.7
33	113.0	121.5	130.1	138.7	147.3	156.0	164.8	173.6	182.4	191.2	200.1	208.9	217.7	226.6	235.4	244.1	252.9	261.6
34	113.6	122.1	130.7	139.3	148.0	156.8	165.5	174.3	183.2	192.0	200.8	209.7	218.6	227.4	236.2	245.0	253.8	262.6
35	114.2	122.8	131.4	140.0	148.7	157.5	166.2	175.1	183.9	192.8	201.6	210.5	219.4	228.2	237.1	245.9	254.7	263.5
36	114.9	123.4	132.0	140.7	149.4	158.2	167.0	175.8	184.7	193.5	202.4	211.3	220.2	229.1	238.0	246.8	255.6	264.4
37	115.5	124.0	132.7	141.4	150.1	158.9	167.7	176.5	185.4	194.3	203.2	212.1	221.0	229.9	238.8	247.7	256.5	265.3
38	116.1	124.7	133.3	142.0	150.8	159.6	168.4	177.3	186.1	195.0	204.0	212.9	221.8	230.7	239.6	248.5	257.4	266.2
39	---	125.3	134.0	142.7	151.5	160.3	169.1	178.0	186.9	195.8	204.7	213.7	222.6	231.5	240.5	249.4	258.3	267.1
40	---	126.0	134.6	143.4	152.2	161.0	169.8	178.7	187.6	196.6	205.5	214.4	223.4	232.4	241.3	250.2	259.2	268.0
41	---	126.6	135.3	144.0	152.8	161.7	170.5	179.4	188.4	197.3	206.2	215.2	224.2	233.2	242.1	251.1	260.0	268.9
42	---	127.2	136.0	144.7	153.5	162.4	171.2	180.2	189.1	198.0	207.0	216.0	225.0	233.9	242.9	251.9	260.9	269.8
43	---	127.9	136.6	145.4	154.2	163.1	172.0	180.9	189.8	198.8	207.7	216.7	225.7	234.7	243.7	252.7	261.7	270.7
44	---	128.5	137.3	146.1	154.9	163.8	172.7	181.6	190.5	199.5	208.5	217.5	226.5	235.5	244.5	253.6	262.6	271.6
45	---	---	137.9	146.7	155.6	164.5	173.4	182.3	191.3	200.2	209.2	218.2	227.3	236.3	245.3	254.4	263.4	272.5
46	---	---	138.6	147.4	156.3	165.1	174.1	183.0	192.0	201.0	210.0	219.0	228.0	237.1	246.1	255.2	264.3	273.3
47	---	---	139.2	148.1	156.9	165.8	174.8	183.7	192.7	201.7	210.7	219.7	228.8	237.8	246.9	256.0	265.1	274.2
48	---	---	139.9	148.7	157.6	166.5	175.5	184.4	193.4	202.4	211.4	220.5	229.5	238.6	247.7	256.8	265.9	275.1
49	---	---	140.5	149.4	158.3	167.2	176.1	185.1	194.1	203.1	212.1	221.2	230.3	239.4	248.5	257.6	266.8	276.0
50	---	---	141.2	150.1	159.0	167.9	176.8	185.8	194.8	203.8	212.9	221.9	231.0	240.1	249.3	258.4	267.6	276.8

Legend: SCT = Saturated Condensing Temperature, R-22.  
 SST = Saturated Suction Temperature, R-22.

- Notes:
1. Data subject to a +/- 5% tolerance.
  2. Data based on 9 degrees Fahrenheit Subcooling & Superheat.
  3. - - - indicates conditions outside of the approved operating range.
  4. Operation outside the range of 14-46 deg F SST or 95-130 SCT is limited.  
 See ACCS publication **AC- 02- 006- 01- 0051** for details.



P.O. Box 500  
899 S. Prairie Lane  
Marshfield, MO 65706  
Phone: (417)859-6067  
Fax: (417)859-2109

Model: HITACHI 6005SC-Z

AMPS -230V/3/60 Hz. HITACHI 6005 COMPRESSOR, REFRIGERANT 22

SCT →	77	81	85	89	93	97	101	105	109	113	117	121	125	129	133	137	141	145
SST																		
5	95.1	102.5	109.6	116.5	123.3	129.9	136.5	143.0	149.6	156.3	163.0	170.0	177.1	184.6	192.3	200.4	209.0	218.0
10	97.9	105.2	112.4	119.3	126.2	132.9	139.6	146.4	153.1	160.0	166.9	174.1	181.4	189.0	196.9	205.1	213.7	222.7
15	100.7	108.0	115.1	122.2	129.1	136.0	142.8	149.7	156.7	163.7	170.8	178.1	185.6	193.4	201.4	209.7	218.3	227.3
20	103.5	110.8	118.0	125.0	132.1	139.1	146.0	153.1	160.2	167.3	174.6	182.1	189.8	197.6	205.7	214.2	222.9	231.9
25	106.3	113.6	120.8	127.9	135.0	142.1	149.2	156.4	163.6	170.9	178.4	186.0	193.7	201.8	210.0	218.5	227.3	236.5
30	109.1	116.4	123.6	130.8	138.0	145.2	152.4	159.6	166.9	174.4	181.9	189.7	197.6	205.7	214.1	222.8	231.7	241.0
31	109.6	117.0	124.2	131.4	138.6	145.8	153.0	160.2	167.6	175.0	182.6	190.4	198.3	206.5	214.9	223.6	232.6	241.9
32	110.2	117.5	124.8	132.0	139.2	146.4	153.6	160.9	168.2	175.7	183.3	191.1	199.1	207.3	215.7	224.4	233.5	242.8
33	110.8	118.1	125.3	132.6	139.7	146.9	154.2	161.5	168.9	176.4	184.0	191.8	199.8	208.1	216.5	225.3	234.3	243.7
34	111.3	118.7	125.9	133.1	140.3	147.5	154.8	162.1	169.5	177.0	184.7	192.5	200.6	208.8	217.3	226.1	235.2	244.6
35	111.9	119.2	126.5	133.7	140.9	148.1	155.4	162.7	170.1	177.7	185.4	193.2	201.3	209.6	218.1	226.9	236.0	245.5
36	112.5	119.8	127.0	134.3	141.5	148.7	156.0	163.3	170.8	178.3	186.0	193.9	202.0	210.3	218.9	227.7	236.9	246.4
37	113.0	120.3	127.6	134.8	142.0	149.3	156.6	163.9	171.4	178.9	186.7	194.6	202.7	211.0	219.6	228.5	237.7	247.2
38	113.6	120.9	128.2	135.4	142.6	149.8	157.1	164.5	172.0	179.6	187.3	195.3	203.4	211.8	220.4	229.3	238.6	248.1
39	---	121.5	128.7	135.9	143.2	150.4	157.7	165.1	172.6	180.2	188.0	195.9	204.1	212.5	221.2	230.1	239.4	249.0
40	---	122.0	129.3	136.5	143.7	151.0	158.3	165.7	173.2	180.8	188.6	196.6	204.8	213.2	221.9	230.9	240.2	249.9
41	---	122.6	129.8	137.1	144.3	151.5	158.8	166.2	173.8	181.4	189.2	197.2	205.4	213.9	222.6	231.7	241.1	250.8
42	---	123.2	130.4	137.6	144.8	152.1	159.4	166.8	174.3	182.0	189.8	197.8	206.1	214.6	223.4	232.5	241.9	251.6
43	---	123.7	130.9	138.2	145.4	152.6	159.9	167.4	174.9	182.6	190.4	198.5	206.8	215.3	224.1	233.2	242.7	252.5
44	---	124.3	131.5	138.7	145.9	153.2	160.5	167.9	175.4	183.1	191.0	199.1	207.4	216.0	224.8	234.0	243.5	253.4
45	---	---	132.0	139.2	146.4	153.7	161.0	168.4	176.0	183.7	191.6	199.7	208.0	216.6	225.5	234.8	244.3	254.3
46	---	---	132.6	139.8	147.0	154.2	161.5	169.0	176.5	184.3	192.2	200.3	208.7	217.3	226.2	235.5	245.1	255.2
47	---	---	133.1	140.3	147.5	154.7	162.1	169.5	177.1	184.8	192.7	200.9	209.3	218.0	226.9	236.3	245.9	256.0
48	---	---	133.7	140.8	148.0	155.2	162.6	170.0	177.6	185.3	193.3	201.4	209.9	218.6	227.6	237.0	246.7	256.9
49	---	---	134.2	141.3	148.5	155.7	163.1	170.5	178.1	185.8	193.8	202.0	210.5	219.2	228.3	237.7	247.5	257.8
50	---	---	134.7	141.9	149.0	156.2	163.6	171.0	178.6	186.4	194.3	202.6	211.1	219.9	229.0	238.5	248.3	258.6

Legend: SCT = Saturated Condensing Temperature, R-22.  
SST = Saturated Suction Temperature, R-22.

- Notes:
1. Data subject to a +/- 5% tolerance.
  2. Data based on 9 degrees Fahrenheit Subcooling & Superheat.
  3. - - - indicates conditions outside of the approved operating range.
  4. Operation outside the range of 14-46 deg F SST or 95-130 SCT is limited.  
See ACCS publication **AC- 02- 006- 01- 0051** for details.



**COMPONENT SPECIALISTS**

P.O. Box 500  
 899 S. Prairie Lane  
 Marshfield, MO 65706  
 Phone: (417)859-6067  
 Fax: (417)859-2109

Model: HITACHI 6005SC-Z

AMPS -460V/3/60 Hz. HITACHI 6005 COMPRESSOR, REFRIGERANT 22

SCT →	77	81	85	89	93	97	101	105	109	113	117	121	125	129	133	137	141	145
SST																		
5	44.6	48.8	52.7	56.5	60.1	63.6	67.0	70.3	73.7	77.0	80.4	83.9	87.6	91.4	95.4	99.6	104.0	108.8
10	46.2	50.3	54.2	58.0	61.6	65.2	68.6	72.0	75.4	78.8	82.3	85.9	89.6	93.4	97.4	101.7	106.2	111.0
15	47.7	51.8	55.7	59.5	63.2	66.7	70.2	73.7	77.1	80.6	84.2	87.8	91.5	95.5	99.5	103.9	108.4	113.2
20	49.2	53.3	57.2	61.0	64.7	68.3	71.8	75.4	78.9	82.4	86.0	89.7	93.5	97.5	101.6	106.0	110.6	115.4
25	50.7	54.8	58.8	62.6	66.3	69.9	73.5	77.0	80.6	84.2	87.9	91.6	95.5	99.5	103.7	108.1	112.8	117.6
30	52.3	56.3	60.3	64.1	67.8	71.5	75.1	78.7	82.3	86.0	89.7	93.6	97.5	101.6	105.8	110.3	114.9	119.9
31	52.6	56.6	60.6	64.4	68.1	71.8	75.4	79.0	82.7	86.4	90.1	93.9	97.9	102.0	106.3	110.7	115.4	120.3
32	52.9	56.9	60.9	64.7	68.4	72.1	75.7	79.4	83.0	86.7	90.5	94.3	98.3	102.4	106.7	111.1	115.8	120.7
33	53.2	57.2	61.2	65.0	68.7	72.4	76.1	79.7	83.4	87.1	90.8	94.7	98.7	102.8	107.1	111.6	116.3	121.2
34	53.5	57.5	61.5	65.3	69.0	72.7	76.4	80.0	83.7	87.4	91.2	95.1	99.1	103.2	107.5	112.0	116.7	121.6
35	53.8	57.8	61.8	65.6	69.3	73.0	76.7	80.4	84.1	87.8	91.6	95.5	99.5	103.6	107.9	112.4	117.1	122.1
36	54.1	58.1	62.1	65.9	69.6	73.3	77.0	80.7	84.4	88.1	92.0	95.9	99.9	104.0	108.4	112.9	117.6	122.5
37	54.4	58.4	62.4	66.2	69.9	73.7	77.3	81.0	84.7	88.5	92.3	96.3	100.3	104.4	108.8	113.3	118.0	122.9
38	54.7	58.7	62.7	66.5	70.3	74.0	77.7	81.4	85.1	88.9	92.7	96.6	100.7	104.9	109.2	113.7	118.4	123.4
39	---	59.0	63.0	66.8	70.6	74.3	78.0	81.7	85.4	89.2	93.1	97.0	101.1	105.3	109.6	114.1	118.9	123.8
40	---	59.3	63.3	67.1	70.9	74.6	78.3	82.0	85.8	89.6	93.4	97.4	101.5	105.7	110.0	114.6	119.3	124.3
41	---	59.6	63.6	67.4	71.2	74.9	78.6	82.4	86.1	89.9	93.8	97.8	101.9	106.1	110.5	115.0	119.7	124.7
42	---	59.9	63.9	67.7	71.5	75.2	79.0	82.7	86.5	90.3	94.2	98.2	102.3	106.5	110.9	115.4	120.2	125.2
43	---	60.2	64.2	68.0	71.8	75.5	79.3	83.0	86.8	90.7	94.6	98.6	102.7	106.9	111.3	115.9	120.6	125.6
44	---	60.6	64.5	68.3	72.1	75.9	79.6	83.4	87.2	91.0	94.9	98.9	103.1	107.3	111.7	116.3	121.1	126.0
45	---	---	64.8	68.6	72.4	76.2	79.9	83.7	87.5	91.4	95.3	99.3	103.5	107.7	112.1	116.7	121.5	126.5
46	---	---	65.1	68.9	72.7	76.5	80.3	84.0	87.9	91.7	95.7	99.7	103.9	108.1	112.6	117.1	121.9	126.9
47	---	---	65.4	69.2	73.0	76.8	80.6	84.4	88.2	92.1	96.0	100.1	104.3	108.5	113.0	117.6	122.4	127.4
48	---	---	65.7	69.5	73.3	77.1	80.9	84.7	88.6	92.5	96.4	100.5	104.6	108.9	113.4	118.0	122.8	127.8
49	---	---	66.0	69.8	73.6	77.4	81.2	85.1	88.9	92.8	96.8	100.9	105.0	109.4	113.8	118.4	123.2	128.2
50	---	---	66.3	70.1	73.9	77.8	81.6	85.4	89.3	93.2	97.2	101.2	105.4	109.8	114.2	118.9	123.7	128.7

Legend: SCT = Saturated Condensing Temperature, R-22.  
 SST = Saturated Suction Temperature, R-22.

- Notes: 1. Data subject to a +/- 5% tolerance.  
 2. Data based on 9 degrees Fahrenheit Subcooling & Superheat.  
 3. --- indicates conditions outside of the approved operating range.  
 4. Operation outside the range of 14-46 deg F SST or 95-130 SCT is limited.  
 See ACCS publication **AC- 02- 006- 01- 0051** for details.



P.O. Box 500  
899 S. Prairie Lane  
Marshfield, MO 65706  
Phone: (417)859-6067  
Fax: (417)859-2109

Model: HITACHI 6005SC-Z

KILOWATTS - 60 Hz. HITACHI 6005 COMPRESSOR, REFRIGERANT 22

SCT → SST	77	81	85	89	93	97	101	105	109	113	117	121	125	129	133	137	141	145
5	29.8	32.7	35.7	38.6	41.5	44.4	47.3	50.2	53.1	55.9	58.8	61.6	64.4	67.2	69.9	72.7	75.4	78.2
10	31.1	34.0	36.9	39.9	42.8	45.7	48.6	51.5	54.4	57.2	60.1	63.0	65.8	68.7	71.5	74.4	77.2	80.0
15	32.3	35.3	38.2	41.1	44.0	47.0	49.9	52.8	55.7	58.6	61.5	64.4	67.3	70.2	73.1	76.0	78.9	81.9
20	33.6	36.6	39.5	42.4	45.4	48.3	51.2	54.1	57.0	59.9	62.8	65.8	68.7	71.6	74.6	77.6	80.6	83.7
25	34.8	37.8	40.8	43.8	46.7	49.6	52.6	55.5	58.4	61.3	64.2	67.1	70.1	73.1	76.1	79.2	82.3	85.5
30	36.1	39.1	42.2	45.1	48.1	51.0	53.9	56.8	59.7	62.6	65.6	68.5	71.5	74.6	77.6	80.8	84.0	87.3
31	36.3	39.4	42.4	45.4	48.3	51.3	54.2	57.1	60.0	62.9	65.8	68.8	71.8	74.8	77.9	81.1	84.4	87.7
32	36.6	39.7	42.7	45.7	48.6	51.5	54.4	57.3	60.3	63.2	66.1	69.1	72.1	75.1	78.3	81.4	84.7	88.0
33	36.8	39.9	43.0	45.9	48.9	51.8	54.7	57.6	60.5	63.4	66.4	69.3	72.4	75.4	78.6	81.8	85.0	88.4
34	37.1	40.2	43.2	46.2	49.2	52.1	55.0	57.9	60.8	63.7	66.6	69.6	72.6	75.7	78.9	82.1	85.4	88.8
35	37.3	40.4	43.5	46.5	49.4	52.3	55.3	58.1	61.1	64.0	66.9	69.9	72.9	76.0	79.2	82.4	85.7	89.1
36	37.6	40.7	43.7	46.7	49.7	52.6	55.5	58.4	61.3	64.2	67.2	70.2	73.2	76.3	79.5	82.7	86.1	89.5
37	37.8	41.0	44.0	47.0	50.0	52.9	55.8	58.7	61.6	64.5	67.4	70.4	73.5	76.6	79.8	83.0	86.4	89.9
38	38.1	41.2	44.3	47.3	50.2	53.1	56.0	58.9	61.8	64.8	67.7	70.7	73.8	76.9	80.1	83.3	86.7	90.2
39	---	41.5	44.5	47.5	50.5	53.4	56.3	59.2	62.1	65.0	68.0	71.0	74.0	77.2	80.4	83.7	87.1	90.6
40	---	41.7	44.8	47.8	50.7	53.7	56.6	59.5	62.4	65.3	68.2	71.2	74.3	77.4	80.7	84.0	87.4	91.0
41	---	42.0	45.0	48.0	51.0	53.9	56.8	59.7	62.6	65.5	68.5	71.5	74.6	77.7	81.0	84.3	87.8	91.3
42	---	42.2	45.3	48.3	51.3	54.2	57.1	60.0	62.9	65.8	68.8	71.8	74.9	78.0	81.3	84.6	88.1	91.7
43	---	42.5	45.6	48.6	51.5	54.4	57.3	60.2	63.1	66.1	69.0	72.1	75.1	78.3	81.6	84.9	88.4	92.1
44	---	42.8	45.8	48.8	51.8	54.7	57.6	60.5	63.4	66.3	69.3	72.3	75.4	78.6	81.9	85.3	88.8	92.4
45	---	---	46.1	49.1	52.0	54.9	57.8	60.7	63.6	66.6	69.6	72.6	75.7	78.9	82.2	85.6	89.1	92.8
46	---	---	46.3	49.3	52.3	55.2	58.1	61.0	63.9	66.8	69.8	72.9	76.0	79.2	82.5	85.9	89.5	93.2
47	---	---	46.6	49.6	52.5	55.4	58.3	61.2	64.1	67.1	70.1	73.1	76.3	79.5	82.8	86.2	89.8	93.5
48	---	---	46.8	49.8	52.7	55.7	58.6	61.5	64.4	67.3	70.3	73.4	76.5	79.8	83.1	86.6	90.2	93.9
49	---	---	47.1	50.0	53.0	55.9	58.8	61.7	64.6	67.6	70.6	73.7	76.8	80.0	83.4	86.9	90.5	94.3
50	---	---	47.3	50.3	53.2	56.1	59.0	61.9	64.9	67.8	70.8	73.9	77.1	80.3	83.7	87.2	90.9	94.7

Legend: SCT = Saturated Condensing Temperature, R-22.  
SST = Saturated Suction Temperature, R-22.

- Notes: 1. Data subject to a +/- 5% tolerance.  
2. Data based on 9 degrees Fahrenheit Subcooling & Superheat.  
3. - - - indicates conditions outside of the approved operating range.  
4. Operation outside the range of 14-46 deg F SST or 95-130 SCT is limited.  
See ACCS publication **AC- 02- 006- 01- 0051** for details.